## TPI ENGINEERED SYSTEMS, INC.

Phone: (804) 232 - 4580



CAPACITY:  (CFH) (LBS/HR) (TPH) (MTPH) (BPH)  PARTICLE SIZE:  BULK DENSITY:  (PCF)  PED BY:  DISCHARGES TO:  (SPECIFY ONE OF THE FOLLOWING)  OVERALL HEIGHT: SHAFT CENTERS: PRODUCT LIFT:  HA  F  T  DRIVE TYPE: BACKSTOP: BACKSTOP: CSHAFT MOUNT / FOOT MOUNT / OTHER BACKSTOP: SSHAFT (SHAFT MOUNT / FOOT MOUNT / OTHER) BACKSTOP: CC BLEVATOR TYPE: CC CC CC CC CONTINUOUS / CENTERFUGAL / CEMENT / SUPER CAPACITY / OTHER CC	BUCKET ELEVATOR DATA SHEET	
CONTROL  Email:  Phone:  Fax:  EQUIPMENT:  MATERIAL:  M		
CONTROL  FAX  EQUIPMENT:  MATERIAL:  (CFH) (LBS/HR) (TPH) (MTPH) (BPH)  PARTICLE SIZE:  BULK DENSITY:  (PCF)  (PCF)  (PCF)  (SPECIFY ONE OF THE FOLLOWING OVERALL HEIGHT: SHAFT CENTERS: PRODUCT LIFT: HONOR DATA: (CARBON / 304SS / 316SS / H0G / OTH) INSTALLATION:		IPI Quote:
EMILE Phone: Fax:  EQUIPMENT:  MATERIAL:  Sk MOISTURE:  TEMP: "F":  CAPACITY:  (CFH) (LBSHR) (TPH) (MTPH) (BPH)  PARTICLE SIZE:  SULK DENSITY:  (PCF)  DISCHARGES TO:  OVERALL HEIGHT: SHAFT CENTERS: PRODUCT LIFT:  MATERIAL OF CONSTRUCTION: INSTALLATION: I		<del></del>
Phone: Fax:  EQUIPMENT:  MATERIAL:  (CFH) (LBSAHR) (TPH) (MTPH) (BPH)  PARTICLE SIZE:  BULK DENSITY:  (PCF)  DISCHARGES TO:  (SPECIFY ONE OF THE FOLLOWING  OVERALL HEIGHT: SHAFT CENTERS: PRODUCT LIFT: NSTALLATION: (CARBON / 3045S/316SS / HDG / OTH) (NEW / REPLACEMENT / INDOORS / OUTD  HP / SPEED IF EXISTING: DRIVE TYPE: BACKSTOP: GSHAFT / INTEGRAL / OTHER)  D PT COMPONENTS: (WBELTS / CHAIN / DIRECT / OTHER)  I MOTOR DATA: TEFC / XPROOP / PREMIUM EFF / OTH  S C ELEVATOR TYPE: C CHAIN OR BELT SPECS: E NET: C STANDARD OR SPECIAL)  B SAFETY CAGE W/ LADDER: C STANDARD OR SPECIAL)  H DISCHARGE: STANDARD OR SPECIAL)  I LADDER LENGTH: C HEAD PLATFORM: H DISCHARGE: C STANDARD OR SPECIAL)  I INTERNEDIATE PLATFORM: (YES / NO) SIZE?: (YES / NO) SIZE?: (YES / NO) OTY ?): HAD THICKNESS:		<del></del>
EQUIPMENT:  MATERIAL:  % MOISTURE:  TEMP. 'F':  CAPACITY:  (CFH) (LBSAHR) (TPH) (MTPH) (BPH)  PARTICLE SIZE:  BULK DENSITY:  (PCF)  DISCHARGES TO:  (SPECIFY ONE OF THE FOLLOWING  OVERALL HEIGHT: SHAFT CENTERS: PRODUCT LIFT:  MATERIAL OF CONSTRUCTION: (CARBON / 304SS / 316SS / HDG / OTH) INSTALLATION: (NEW / REPLACEMENT / INDOORS / OUTD  HP / SPEED IF EXISTING: DRIVE TYPE: (SHAFT / INTEGRAL / OTHER)  D PT COMPONENTS: (V-BELTS / CHAIN / DIRECT / OTHER)  BACKSTOP: (SHAFT / INTEGRAL / OTHER)  T MOTOR DATA: (CENTINUOUS / CENTIFUGAL / CEMENT / SUPER CAPACITY / OTHER)  C ELEVATOR TYPE: (CONTINUOUS / CENTIFUGAL / CEMENT / SUPER CAPACITY / OTHER)  R ELEVATOR TYPE: (CHAIN OR BELT)  G CHAIN OR BELT SPECS:  E  H DISCHARGE: (STANDARD OR SPECIAL)  BE SAFETY CAGE WI LADDER: (YES / NO) LADDER LENGTH:  G HAD PLATFORM: (YES / NO) OTY /?: HEAD THICKNESS:		<u> </u>
MATERIAL:  (CFH) (LBS/HR) (TPH) (MTPH) (BPH)  PARTICLE SIZE:  (SPECIFY ONE OF THE FOLLOWING  OVERALL HEIGHT:  SHAFT CENTERS; PRODUCT LIFT:  MATERIAL OF CONSTRUCTION: (SPECIFY ONE OF THE FOLLOWING)  (CARBON / 304SS / 316SS / HDG / OTH) (NEW / REPLACEMENT / INDOORS / OUTD  HP / SPEED IF EXISTING: DRIVE TYPE: I MOTOR DATA: (SHAFT MOUNT / FOOT MOUNT / OTH) B BACKSTOP: (SHAFT MOUNT / FOOT MOUNT / OTH) B BACKSTOP: (SHAFT MOUNT / FOOT MOUNT / OTH) C G ELEVATOR TYPE: (CONTINUOUS / CENTRIFUGAL / CEMENT / SUPER CAPACITY / OTH) A C C ELEVATOR TYPE: C G CHAIN OR BELT SPECS: E INLET: G CHAIN OR BELT SPECS: E INLET: G CHAIN OR BELT SPECS: E INLET: G CHAIN OR SPECIAL) G CHAIN OR SPECIAL G CHAIN OR SPE		<u> </u>
MATERIAL:  (CFH) (LBS/HR) (TPH) (MTPH) (BPH)  PARTICLE SIZE:  (SPECIFY ONE OF THE FOLLOWING  OVERALL HEIGHT:  SHAFT CENTERS; PRODUCT LIFT:  MATERIAL OF CONSTRUCTION: (SPECIFY ONE OF THE FOLLOWING)  (CARBON / 304SS / 316SS / HDG / OTH) (NEW / REPLACEMENT / INDOORS / OUTD  HP / SPEED IF EXISTING: DRIVE TYPE: I MOTOR DATA: (SHAFT MOUNT / FOOT MOUNT / OTH) B BACKSTOP: (SHAFT MOUNT / FOOT MOUNT / OTH) B BACKSTOP: (SHAFT MOUNT / FOOT MOUNT / OTH) C G ELEVATOR TYPE: (CONTINUOUS / CENTRIFUGAL / CEMENT / SUPER CAPACITY / OTH) A C C ELEVATOR TYPE: C G CHAIN OR BELT SPECS: E INLET: G CHAIN OR BELT SPECS: E INLET: G CHAIN OR BELT SPECS: E INLET: G CHAIN OR SPECIAL) G CHAIN OR SPECIAL G CHAIN OR SPE		
CAPACITY: (CFH) (LBS/HR) (TPH) (MTPH) (BPH)  PARTICLE SIZE:  BULK DENSITY: (PCF)  PED BY: DISCHARGES TO:  (SPECIFY ONE OF THE FOLLOWING  OVERALL HEIGHT: SHAFT CENTERS; PRODUCT LIFT: PRODUCT LIFT:  MATERIAL OF CONSTRUCTION: (CARBON / 304SS / 316SS / HDG / OTH) INSTALLATION: (NEW / REPLACEMENT / INDOORS / OUTD  HP / SPEED IF EXISTING: HP  BACKSTOP: GSHAFT / INTEGRAL / OTHER) I MOTOR DATA: I (TEFC / XPROOF / PREMIUM EFF / OTH  S C ELEVATOR TYPE: (CONTINUOUS / CENTERFUGAL / CEMENT / SUPER CAPACITY / OTHER) A ELEVATOR TYPE: C CHAIN OR BELT SPECS: E INLET: GCHAIN OR BELT SPECS: E INLET: GSTANDARD OR SPECIAL) I LADDER LENGTH: GHAP CAPACITY / OTHER  HEAD THICKNESS:  (YES / NO) SIZE?: INTERMEDIATE PLATFORM: (YES / NO) SIZE?: INTERMEDIATE PLATFORM: (YES / NO) SIZE?: (		
SULK DENSITY: (PCF)  FED BY: DISCHARGES TO:  (SPECIFY ONE OF THE FOLLOWING OVERALL HEIGHT: SHAFT CENTERS; PRODUCT LIFT:  MATERIAL OF CONSTRUCTION: (CARBON / 304SS / 316SS / HDG / OTH) INSTALLATION: (NEW / REPLACEMENT / INDOORS / OUT)  HP / SPEED IF EXISTING: HP DRIVE TYPE: (SHAFT / MOUNT / FOOT MOUNT / OTHER) BACKSTOP: (SHAFT / INTEGRAL / OTHER) I MOTOR DATA: (TEFC / XPROOF / PREMIUM EFF / OTH S C ELEVATOR TYPE: (CONTINUOUS / CENTRIFUGAL / CEMENT / SUPER CAPACITY / OTHE A R ELEVATOR TYPE: (CHAIN OR BELT) C CHAIN OR BELT SPECS: E INLET: (STANDARD OR SPECIAL) DISCHARGE: (STANDARD OR SPECIAL) I SAFETY CAGE W/ LADDER: (STANDARD OR SPECIAL) I LADDER LENGTH:  H HEAD THICKNESS:  HEAD THICKNESS:  (YES / NO) SIZE?: (YES / NO) GTY.?):	% MOISTURE:	TEMP. "F":
DISCHARGES TO:  (SPECIFY ONE OF THE FOLLOWING  OVERALL HEIGHT: SHAFT CENTERS: PRODUCT LIFT:  MATERIAL OF CONSTRUCTION: (INSTALLATION: (INSTAL	(CFH) (LBS/HR) (TPH) (MTPH) (E	PARTICLE SIZE:
OVERALL HEIGHT: SHAFT CENTERS: PRODUCT LIFT:  MATERIAL OF CONSTRUCTION: INSTALLATION:  HP / SPEED IF EXISTING: BACKSTOP: INSTALLATION: INSTALLATION: OVERALL FEINST ING: INSTALLATION: OVERALL AND INSTALLATION: OVERALL AND INSTALLATION: OVERALL / ONLY / ONLY / OTHER BACKSTOP: INSTALLATION: OVERALL / ONLY / OTHER INSTALLATION: OVERALL / ONLY / OTHER INSTALLATION: OVERALL / ONLY / ONLY / OTHER INSTALLATION: OVERAL / ONLY / OTHER INSTALLATION: OVERALL / ONLY / OTHER INSTALLATION		3Y:
OVERALL HEIGHT: SHAFT CENTERS; PRODUCT LIFT:  MATERIAL OF CONSTRUCTION: (CARBON / 304SS / 316SS / HDG / OTH- INSTALLATION: (NEW / REPLACEMENT / INDOORS / OUTD  HP / SPEED IF EXISTING: HP DRIVE TYPE: (SHAFT / INTEGRAL / OTHER) BACKSTOP: (SHAFT / INTEGRAL / OTHER) I MOTOR DATA: (TEFC / XPROOF / PREMIUM EFF / OTH S C ELEVATOR TYPE: (CHAIN / DIRECT / OTHER I MOTOR DATA: (TEFC / XPROOF / PREMIUM EFF / OTH A R ELEVATOR TYPE: (CHAIN OR BELT)  G CHAIN OR BELT SPECS: E INLET: (STANDARD OR SPECIAL) G SAFETY CAGE W/ LADDER: (YES / NO)  I LADDER LENGTH: G H HEAD PLATFORM: (YES / NO) SIZE?: INTERMEDIATE PLATFORM: (YES / NO) QTY.?: HEAD THICKNESS:	DIS	O:
SHAFT CENTERS: PRODUCT LIFT:  MATERIAL OF CONSTRUCTION: INSTALLATION:  HP / SPEED IF EXISTING: DRIVE TYPE: BACKSTOP: GARDY / SPEED IF EXISTING: WORD ROTER / OTHER)  PT COMPONENTS: (V-BELTS / CHAIN / DIRECT / OTHER)  NOTOR DATA:  CONTINUOUS / CENTRIFUGAL / CEMENT / SUPER CAPACITY / OTHER  R ELEVATOR TYPE: GCHAIN OR BELT SPECS: E INLET: SAFETY CAGE W/ LADDER: CHAIN OR SPECIAL)  LADDER LENGTH: GHAP A PLATFORM: CYES / NO)  LADDER LENGTH:  H HEAD PLATFORM: CYES / NO) CYES / NO) CTYPE: CYES / NO) CYES / NO) CYES / NO) CYES / NO) CTYPE: CYES / NO) CYES / NO	0.//	(SPECIFY ONE OF THE FOLLOWING)
PRODUCT LIFT:  MATERIAL OF CONSTRUCTION: (CARBON / 304SS / 316SS / HDG / OTH INSTALLATION: (NEW / REPLACEMENT / INDOORS / OUTD  HP / SPEED IF EXISTING: HP  DRIVE TYPE: (SHAFT MOUNT / FOOT MOUNT / OTHE BACKSTOP: (SHAFT / INTEGRAL / OTHER) I MOTOR DATA: (TEFC / XPROOF / PREMIUM EFF / OTH S  C ELEVATOR TYPE: (CONTINUOUS / CENTRIFUGAL / CEMENT / SUPER CAPACITY / OTHE A  R ELEVATOR TYPE: (CHAIN OR BELT)  G CHAIN OR BELT SPECS: E  INLET: (STANDARD OR SPECIAL)  H DISCHARGE: (STANDARD OR SPECIAL)  C SAFETY CAGE W/ LADDER: (YES / NO)  LADDER LENGTH:  HEAD PLATFORM: (YES / NO) SIZE?: INTERMEDIATE PLATFORM: (YES / NO) QTY.?: HEAD THICKNESS: "	OVE	25.
INSTALLATION: (NEW / REPLACEMENT / INDOORS / OUTD  HP / SPEED IF EXISTING: HP  DRIVE TYPE: (SHAFT MOUNT / FOOT MOUNT / OTHER BACKSTOP: (SHAFT / INTEGRAL / OTHER) I MOTOR DATA: (V-BELTS / CHAIN / DIRECT / OTHER S C ELEVATOR TYPE: H (CONTINUOUS / CENTRIFUGAL / CEMENT / SUPER CAPACITY / OTHER C CHAIN OR BELT SPECS: E  INLET: (STANDARD OR SPECIAL) I CSTANDARD OR SPECIAL) I CSTANDARD OR SPECIAL I CSTANDARD OR SPECI		
INSTALLATION: (NEW / REPLACEMENT / INDOORS / OUTD  HP / SPEED IF EXISTING: HP  DRIVE TYPE: (SHAFT MOUNT / FOOT MOUNT / OTHER BACKSTOP: (SHAFT / INTEGRAL / OTHER) I MOTOR DATA: (V-BELTS / CHAIN / DIRECT / OTHER S C ELEVATOR TYPE: H (CONTINUOUS / CENTRIFUGAL / CEMENT / SUPER CAPACITY / OTHER C CHAIN OR BELT SPECS: E  INLET: (STANDARD OR SPECIAL) I CSTANDARD OR SPECIAL) I CSTANDARD OR SPECIAL I CSTANDARD OR SPECI	MATERIAL OF CC	DN:(CARBON / 304SS / 316SS / HDG / OTHER
HP/SPEED IF EXISTING: DRIVE TYPE: BACKSTOP: BACKSTOP: CSHAFT /INTEGRAL / OTHER)  DPT COMPONENTS: CSHAFT /INTEGRAL / OTHER) CSHAFT / INTEGRAL / OTHER) CSHAFT / INTEGRAL / OTHER) CSHAFT / INTEGRAL / CEMENT / SUPER CAPACITY / OTHER CONTINUOUS / CENTRIFUGAL / CEMENT / SUPER CAPACITY / OTHER CHAIN OR BELT SPECS: ENLIET: CSTANDARD OR SPECIAL) CSTANDARD OR SPECIAL CSTANDARD O		
BACKSTOP: (SHAFT / INTEGRAL / OTHER)  D PT COMPONENTS: (V-BELTS / CHAIN / DIRECT / OTHER)  I MOTOR DATA: (TEFC / XPROOF / PREMIIUM EFF / OTHER)  C ELEVATOR TYPE: (CONTINUOUS / CENTRIFUGAL / CEMENT / SUPER CAPACITY / OTHER)  A R ELEVATOR TYPE: (CHAIN OR BELT)  G CHAIN OR BELT SPECS: E  INLET: (STANDARD OR SPECIAL)  H DISCHARGE: (STANDARD OR SPECIAL)  E SAFETY CAGE W / LADDER: (YES / NO)  I LADDER LENGTH: (YES / NO) SIZE?:  T INTERMEDIATE PLATFORM: (YES / NO) QTY.?:  HEAD THICKNESS: "	HP / SPEE	IG:HP
D PT COMPONENTS: (V-BELTS/CHAIN/DIRECT/OTHER  MOTOR DATA: (TEFC/XPROOF/PREMIUM EFF/OTH  S C ELEVATOR TYPE: (CONTINUOUS/CENTRIFUGAL/CEMENT/SUPER CAPACITY/OTHE  A R ELEVATOR TYPE: (CHAIN OR BELT)  G CHAIN OR BELT SPECS: E  INLET: (STANDARD OR SPECIAL)  H DISCHARGE: (STANDARD OR SPECIAL)  E SAFETY CAGE W/LADDER: (YES/NO)  I LADDER LENGTH: (YES/NO)  H HEAD PLATFORM: (YES/NO) SIZE?:  T INTERMEDIATE PLATFORM: (YES/NO) QTY.?:  HEAD THICKNESS: "		
MOTOR DATA: (TEFC / XPROOF / PREMIIUM EFF / OTH  S C ELEVATOR TYPE: (CONTINUOUS / CENTRIFUGAL / CEMENT / SUPER CAPACITY / OTHE  A R ELEVATOR TYPE: (CHAIN OR BELT)  G CHAIN OR BELT SPECS: E INLET: (STANDARD OR SPECIAL) (STANDARD OR SPECIAL) (STANDARD OR SPECIAL)  E SAFETY CAGE W / LADDER: (YES / NO)  I LADDER LENGTH: G H HEAD PLATFORM: (YES / NO) SIZE?: T INTERMEDIATE PLATFORM: (YES / NO) QTY.?: HEAD THICKNESS: "		
S C ELEVATOR TYPE: (CONTINUOUS / CENTRIFUGAL / CEMENT / SUPER CAPACITY / OTHE A R ELEVATOR TYPE: (CHAIN OR BELT)  G CHAIN OR BELT SPECS: E  INLET: (STANDARD OR SPECIAL)  DISCHARGE: (STANDARD OR SPECIAL)  E SAFETY CAGE W / LADDER: (YES / NO)  I LADDER LENGTH: G H HEAD PLATFORM: (YES / NO) SIZE?: INTERMEDIATE PLATFORM: (YES / NO) QTY.?: HEAD THICKNESS: "		
C ELEVATOR TYPE:  (CONTINUOUS / CENTRIFUGAL / CEMENT / SUPER CAPACITY / OTHE  A R ELEVATOR TYPE: (CHAIN OR BELT)  G CHAIN OR BELT SPECS:  E INLET: (STANDARD OR SPECIAL)  H DISCHARGE: (STANDARD OR SPECIAL)  E SAFETY CAGE W / LADDER: (YES / NO)  I LADDER LENGTH:  G H HEAD PLATFORM: (YES / NO) SIZE?:  T INTERMEDIATE PLATFORM: (YES / NO) QTY.?:  HEAD THICKNESS: "		TA: (TEFC / XPROOF / PREMITUM EFF / OTHER
H (CONTINUOUS / CENTRIFUGAL / CEMENT / SUPER CAPACITY / OTHER  R ELEVATOR TYPE: (CHAIN OR BELT)  G CHAIN OR BELT SPECS:  E INLET: (STANDARD OR SPECIAL)  H DISCHARGE: (STANDARD OR SPECIAL)  E SAFETY CAGE W / LADDER: (YES / NO)  I LADDER LENGTH:  G H HEAD PLATFORM: (YES / NO) SIZE?:  T INTERMEDIATE PLATFORM: (YES / NO) QTY.?:  HEAD THICKNESS: "		DE-
R ELEVATOR TYPE: (CHAIN OR BELT)  G CHAIN OR BELT SPECS:  E  INLET: (STANDARD OR SPECIAL)  H DISCHARGE: (STANDARD OR SPECIAL)  E SAFETY CAGE W/ LADDER: (YES / NO)  I LADDER LENGTH:  G  H HEAD PLATFORM: (YES / NO) SIZE?:  T INTERMEDIATE PLATFORM: (YES / NO) QTY.?:  HEAD THICKNESS: "	H (CONTIN	
G CHAIN OR BELT SPECS:  E INLET: (STANDARD OR SPECIAL)  H DISCHARGE: (STANDARD OR SPECIAL)  E SAFETY CAGE W/LADDER: (YES/NO)  I LADDER LENGTH:  G H HEAD PLATFORM: (YES/NO) SIZE?:  T INTERMEDIATE PLATFORM: (YES/NO) QTY.?:  HEAD THICKNESS: "		OF. (OHAIN OR RELT)
INLET: (STANDARD OR SPECIAL)  H DISCHARGE: (STANDARD OR SPECIAL)  E SAFETY CAGE W/ LADDER: (YES / NO)  I LADDER LENGTH:  G H HEAD PLATFORM: (YES / NO) SIZE?:  T INTERMEDIATE PLATFORM: (YES / NO) QTY.?:  HEAD THICKNESS: "		
H DISCHARGE: (STANDARD OR SPECIAL)  E SAFETY CAGE W/LADDER: (YES/NO)  I LADDER LENGTH:  G H HEAD PLATFORM: (YES/NO) SIZE?:  T INTERMEDIATE PLATFORM: (YES/NO) QTY.?:  HEAD THICKNESS: "	E	ET: (STANDARD OR SPECIAL)
E SAFETY CAGE W/LADDER: (YES/NO)  I LADDER LENGTH:  G H HEAD PLATFORM: (YES/NO) SIZE?:  T INTERMEDIATE PLATFORM: (YES/NO) QTY.?:  HEAD THICKNESS: "	н	
LADDER LENGTH:		
H         HEAD PLATFORM:         (YES / NO)         SIZE?:           T         INTERMEDIATE PLATFORM:         (YES / NO)         QTY.?:           HEAD THICKNESS:         "	I LAD	
HEAD THICKNESS: "		M: (YES / NO) SIZE?:
		· · · · · · · · · · · · · · · · · · ·
BOOT THICKNESS: "  INTERMEDIATE THICKNESS: "		
TAKE-UP: (HEAD / BOOT) (SCREW / GRAVITY)		JP: (HEAD / BOOT) (SCREW / GRAVITY)
SEALS: (STANDARD / SPECIAL)		LS: (STANDARD / SPECIAL)
Paint:		aint:
NOTES:		-